

SATU


Ø21.8 mm 3 lens array for up to 3535 size LED packages

SATU lens family is the smallest 3 lens array on the market. Due to its compact size and beam selection, it is an ideal choice for jewellery shops, museums, reading lights, compact torches, head lamps and track lights. The flange enables the easy addition of an O-ring or faceplate without overlapping with optical surfaces.



PRODUCTS:

C11544_SATU-W



Dimensions: 21.8 mm x 21.8 mm
Height: 8.90 mm
~35° wide beam

C11602_SATU-M

SetPlotAreaWorld(1): X range error - min >= max

Dimensions: 21.8 mm x 21.8 mm
Height: 8.90 mm
~30° medium beam


C11916_SATU-S

SetPlotAreaWorld(1): X range error - min >= max

Dimensions: 21.8 mm x 21.8 mm
Height: 8.90 mm
~19° spot beam

PRODUCTS:

C11917_SATU-O




Dimensions: 21.8 mm x 21.8 mm

Height: 8.90 mm

~40° + 20° oval beam

C13234_SATU-S




Dimensions: 21.8 mm x 21.8 mm

Height: 8.90 mm

~19° spot beam optimized for CREE
XT-E

C13235_SATU-W




Dimensions: 21.8 mm x 21.8 mm

Height: 8.90 mm

~35° wide beam optimized for CREE
XT-E

C13297_SATU-O



Dimensions: 21.8 mm x 21.8 mm

Height: 8.90 mm

~40° + 20° oval beam optimized for
CREE XT-E

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)