

SATU-S

~19° spot beam optimized for CREE XT-E


TECHNICAL SPECIFICATIONS:

Dimensions	Ø 21.8 mm
Height	8.9 mm
Fastening	glue, pin
Colour	clear
Box size	480 x 280 x 300 mm
Box weight	7.7 kg
Quantity in Box	2880 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:


Component	Type	Material	Colour
SATU-S	Multi-lens	PMMA	clear



PHOTOMETRIC DATA (MEASURED):


CREE

LED XB-D
FWHM 21.0°
Efficiency 80 %
Peak intensity 3.500 cd/lm
LEDs/each optic 1
Light colour White
Required components:





CREE

LED XP-E
FWHM 20.0°
Efficiency 85 %
Peak intensity 4.600 cd/lm
LEDs/each optic 1
Light colour White
Required components:




CREE

LED XP-E2
FWHM 20.0°
Efficiency 86 %
Peak intensity 5.500 cd/lm
LEDs/each optic 1
Light colour White
Required components:



CREE



LED XP-G
FWHM 25.0°
Efficiency 83 %
Peak intensity 2.900 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (MEASURED):





LED XP-G2
FWHM 26.0°
Efficiency 85 %
Peak intensity 3.300 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED XT-E
FWHM 24.0°
Efficiency 89 %
Peak intensity 3.400 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED H35B0 (LEMWA32)
FWHM 24.0°
Efficiency 82 %
Peak intensity 3.200 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED H35C0 (LEMWA33)
FWHM 27.0°
Efficiency 86 %
Peak intensity 2.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):




LED LUXEON T
FWHM 27.0°
Efficiency 88 %
Peak intensity 2.700 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED LUXEON TX
FWHM 26.0°
Efficiency 86 %
Peak intensity 2.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NF2x757A
FWHM 23.0°
Efficiency 85 %
Peak intensity 2.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED Oslon Square EC
FWHM 24.0°
Efficiency 85 %
Peak intensity 3.200 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (MEASURED):

OSRAM



Opto Semiconductors

LED Oslon SSL 80
FWHM 18.0°
Efficiency 81 %
Peak intensity 4.400 cd/lm
LEDs/each optic 1
Light colour White
Required components:



SAMSUNG


LED LH351Z
FWHM 24.0°
Efficiency 87 %
Peak intensity 3.400 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):




LED LUXEON H50-2
FWHM 24.0°
Efficiency 90 %
Peak intensity 4.000 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED NVSxx19B/NVSxx19C
FWHM 26.0°
Efficiency 87 %
Peak intensity 3.130 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED Synios P2720 1/2 mm
FWHM 16.0°
Efficiency 94 %
Peak intensity 7.890 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED Z8Y22P
FWHM 27.0°
Efficiency 87 %
Peak intensity 2.690 cd/lm
LEDs/each optic 1
Light colour White
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)