

OLGA-S

~11° spot beam beam. Assembly with holder and installation tape.


TECHNICAL SPECIFICATIONS:

Dimensions	Ø 32.0 mm
Height	19.1 mm
Fastening	tape, pin
Colour	black
Box size	476 x 273 x 292 mm
Box weight	9.8 kg
Quantity in Box	792 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:


Component	Type	Material	Colour
OLGA-S	Single lens	PMMA	clear
OLGA-HLD	Holder	PC	black
SPUTNIK-TAPE3	Tape	PU tape	black




PHOTOMETRIC DATA (MEASURED):





LED XD16
FWHM 13.0°
Efficiency 82 %
Peak intensity 10.400 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED XHP35 HD
FWHM 19.0°
Efficiency 83 %
Peak intensity 5.500 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XHP35 HI
FWHM 15.0°
Efficiency 87 %
Peak intensity 8.500 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED XHP50
FWHM 24.0°
Efficiency 83 %
Peak intensity 3.700 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):




LED XHP50.2
FWHM 23.0°
Efficiency 82 %
Peak intensity 4.000 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED XM-L
FWHM 17.0°
Efficiency 86 %
Peak intensity 6.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XP-E
FWHM 11.0°
Efficiency 87 %
Peak intensity 12.100 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED XP-E2
FWHM 11.0°
Efficiency 89 %
Peak intensity 13.600 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):





LED XP-G2
FWHM 13.0°
Efficiency 87 %
Peak intensity 10.000 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED XP-G3
FWHM 14.0°
Efficiency 86 %
Peak intensity 8.400 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XP-L HI
FWHM 14.0°
Efficiency 88 %
Peak intensity 10.200 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED XP-L2
FWHM 18.0°
Efficiency 82 %
Peak intensity 5.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):





LED XQ-E HD
FWHM 11.0°
Efficiency 81 %
Peak intensity 11.000 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED XQ-E HI
FWHM 11.0°
Efficiency 86 %
Peak intensity 13.600 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XT-E
FWHM 14.0°
Efficiency 84 %
Peak intensity 8.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED LUXEON C
FWHM 11.0°
Efficiency 84 %
Peak intensity 11.600 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):




LED LUXEON CZ
FWHM 11.0°
Efficiency 89 %
Peak intensity 14.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED LUXEON M/MX
FWHM 24.0°
Efficiency 84 %
Peak intensity 3.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON MZ
FWHM 19.0°
Efficiency 86 %
Peak intensity 6.300 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED LUXEON Rebel ES
FWHM 14.0°
Efficiency 86 %
Peak intensity 9.500 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):



LUMILEDS

LED LUXEON TX
FWHM 14.0°
Efficiency 86 %
Peak intensity 9.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LUMILEDS

LED LUXEON V
FWHM 18.0°
Efficiency 84 %
Peak intensity 6.500 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LUMILEDS

LED LUXEON V2
FWHM 15.0°
Efficiency 86 %
Peak intensity 9.000 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LUMILEDS



LED LUXEON Z
FWHM 11.0°
Efficiency 88 %
Peak intensity 15.100 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (MEASURED):





LED LUXEON Z ES
FWHM 12.0°
Efficiency 89 %
Peak intensity 12.100 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED NCSxE17A
FWHM 12.0°
Efficiency 87 %
Peak intensity 12.700 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NVSW219D
FWHM 14.0°
Efficiency 85 %
Peak intensity 9.300 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED NVSW319B
FWHM 16.0°
Efficiency 86 %
Peak intensity 7.400 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):





LED NVSxE21A
FWHM 14.0°
Efficiency 87 %
Peak intensity 10.300 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED NVSxx19B/NVSxx19C
FWHM 15.0°
Efficiency 85 %
Peak intensity 8.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED Duris S8
FWHM 24.0°
Efficiency 86 %
Peak intensity 4.300 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED OSCONIQ P 3737 (2W version)
FWHM 14.0°
Efficiency 87 %
Peak intensity 9.200 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):

OSRAM

Opto Semiconductors



LED OSCONIQ P 3737 (3W version)
FWHM 17.0°
Efficiency 86 %
Peak intensity 7.200 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM

Opto Semiconductors



LED OSCONIQ P 7070
FWHM 23.0°
Efficiency 84 %
Peak intensity 4.100 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM

Opto Semiconductors



LED OSLON Black Flat
FWHM 11.0°
Efficiency 88 %
Peak intensity 16.000 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM

Opto Semiconductors


LED OSLON Square CSSRM2/CSSRM3
FWHM 14.0°
Efficiency 87 %
Peak intensity 10.200 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):


OSRAM
Opto Semiconductors

LED OSLON Square EC
FWHM 13.0°
Efficiency 85 %
Peak intensity 10.000 cd/lm
LEDs/each optic 1
Light colour White
Required components:





OSRAM
Opto Semiconductors

LED OSLON Square PC
FWHM 13.0°
Efficiency 85 %
Peak intensity 10.100 cd/lm
LEDs/each optic 1
Light colour White
Required components:




OSRAM
Opto Semiconductors

LED OSLON SSL 150
FWHM 11.0°
Efficiency 87 %
Peak intensity 13.000 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM
Opto Semiconductors



LED OSLON SSL 80
FWHM 13.0°
Efficiency 86 %
Peak intensity 11.100 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):



SAMSUNG

LED LH181A
FWHM 15.0°
Efficiency 81 %
Peak intensity 8.400 cd/m
LEDs/each optic 1
Light colour White
Required components:





SAMSUNG

LED LH181B
FWHM 15.0°
Efficiency 87 %
Peak intensity 9.700 cd/m
LEDs/each optic 1
Light colour White
Required components:





SAMSUNG

LED LH231B
FWHM 16.0°
Efficiency 88 %
Peak intensity 8.600 cd/m
LEDs/each optic 1
Light colour White
Required components:



SAMSUNG



LED LH351B
FWHM 14.0°
Efficiency 87 %
Peak intensity 9.300 cd/m
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):



SAMSUNG

LED LH351C
FWHM 15.0°
Efficiency 86 %
Peak intensity 8.500 cd/lm
LEDs/each optic 1
Light colour White
Required components:




SAMSUNG

LED LH351D
FWHM 18.0°
Efficiency 85 %
Peak intensity 6.200 cd/lm
LEDs/each optic 1
Light colour White
Required components:




SAMSUNG

LED LH508A
FWHM 21.0°
Efficiency 86 %
Peak intensity 4.900 cd/lm
LEDs/each optic 1
Light colour White
Required components:



SAMSUNG



LED LM302A
FWHM 14.0°
Efficiency 89 %
Peak intensity 9.900 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):



SAMSUNG

LED LM561B
FWHM 14.0°
Efficiency 88 %
Peak intensity 9.300 cd/lm
LEDs/each optic 1
Light colour White
Required components:



SEOUL SEMICONDUCTOR


LED Z5M3
FWHM 16.0°
Efficiency 84 %
Peak intensity 7.700 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):




LED XHP50
FWHM 23.0°
Efficiency 86 %
Peak intensity 4.639 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON MZ
FWHM 18.0°
Efficiency 90 %
Peak intensity 7.594 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NFMW48xA
FWHM 21.0°
Efficiency 89 %
Peak intensity 5.460 cd/lm
LEDs/each optic 1
Light colour White
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salu, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)