


T491, Tantalum, MnO2 Tantalum, 33 uF, 20%, 6.3 VDC, SMD, MnO2, Molded, 1.6 Ohms, 6032, Height Max = 2.8mm



### General Information

<b>Series:</b>	T491
<b>Dielectric:</b>	MnO2 Tantalum
<b>Style:</b>	SMD Chip
<b>Description:</b>	SMD, MnO2, Molded
<b>RoHS:</b>	Yes
<b>Termination:</b>	Tin
<b>AEC-Q200:</b>	No
<b>Component Weight:</b>	224.48 mg
<b>Shelf Life:</b>	156 Weeks
<b>MSL:</b>	1

### Dimensions

<b>Footprint</b>	6032
<b>L</b>	6mm +/-0.3mm
<b>W</b>	3.2mm +/-0.3mm
<b>H</b>	2.5mm +/-0.3mm
<b>T</b>	0.13mm REF
<b>S</b>	1.3mm +/-0.3mm
<b>F</b>	2.2mm +/-0.1mm
<b>A</b>	2.9mm MIN
<b>B</b>	0.5mm +/-0.15mm
<b>E</b>	2.4mm REF
<b>G</b>	2.8mm REF
<b>P</b>	0.9mm REF
<b>R</b>	1mm REF
<b>X</b>	0.1mm +/-0.1mm

### Specifications

<b>Capacitance:</b>	33 uF
<b>Capacitance Tolerance:</b>	20%
<b>Voltage DC:</b>	6.3 VDC (85C), 4.22 VDC (125C)
<b>Temperature Range:</b>	-55/+125°C
<b>Rated Temperature:</b>	85°C
<b>Dissipation Factor:</b>	6% 120Hz 25C
<b>Failure Rate:</b>	N/A
<b>Resistance:</b>	1.6 Ohms (100kHz 25C)
<b>Ripple Current:</b>	247 mA (rms, 100kHz 25C), 222.3 mA (rms, 85C), 98.8 mA (rms, 125C)
<b>Leakage Current:</b>	2.1 uA (5min 25°C)

### Packaging Specifications

<b>Packaging:</b>	T&R, 178mm
<b>Packaging Quantity:</b>	500