

RONDA


Low profile lenses with wide customization possibilities to cover all indoor lighting needs compatible with up to 14 mm LES size COBs and LEDiL HEKLA sockets/connectors.

RONDA is part of LEDiL's platform of modular light engines with very wide customization possibilities. Supporting different base parts and numerous front panel fastening methods it can be adapted to a wide range of applications. Whether used in museums, offices or for architectural purposes the same modular solution can be used with different beam patterns as well. Three holders: Holder A for LEDiL twist and lock base parts + 3rd party connectors (TE, Bender+Wirth, Ideal), Holder B for 3rd party connectors (BJB, Ideal, Stucchi) and Holder C for LEDiL HEKLA.



PRODUCTS:


FN15736_RONDA-WW-B



Dimensions: 69.9 mm x 69.9 mm
Height: 14.60 mm

~60° wide beam with holder B
compatible with 3rd party connectors
from BJB, IDEAL and Stucchi


FN15737_RONDA-WWW-B



Dimensions: 69.9 mm x 69.9 mm
Height: 14.60 mm

~90° very wide beam with holder B
compatible with 3rd party connectors
from BJB, IDEAL and Stucchi.

FN15738_RONDA-REC-60-B




Dimensions: 69.9 mm x 69.9 mm
Height: 14.60 mm

~60° + 60° rectangular beam with
holder B compatible with 3rd party
connectors from BJB, IDEAL and
Stucchi

PRODUCTS:


FN15789_RONDA-REC-90



Dimensions: 69.9 mm x 69.9 mm
Height: 14.60 mm

~80° rectangular beam with holder B
compatible with 3rd party connectors
from BJB, IDEAL and Stucchi


FN15792_RONDA-REC-90-B



Dimensions: 69.9 mm x 69.9 mm
Height: 14.60 mm

~80° rectangular beam with holder B
compatible with 3rd party connectors
from BJB, IDEAL and Stucchi


FN15966_RONDA-WWW-C



Dimensions: 53.9 mm x 53.9 mm
Height: 17.00 mm

~90° wide beam with holder C
compatible with LEDiL HEKLA


FN15968_RONDA-WW-C



Dimensions: 53.9 mm x 53.9 mm
Height: 16.90 mm

~60° wide beam with holder C
compatible with LEDiL HEKLA


FN15969_RONDA-W-C



Dimensions: 52.1 mm x 52.1 mm
Height: 16.98 mm

~45° wide beam with holder C
compatible with LEDiL HEKLA

FN15970_RONDA-S-C




Dimensions: 52.1 mm x 52.1 mm
Height: 17.20 mm

~25° spot beam with holder C
compatible with LEDiL HEKLA

PRODUCTS:


FN15971_RONDA-WAS-C



Dimensions: 53.9 mm x 53.9 mm
Height: 24.65 mm

Asymmetric beam for wall washing
with holder C compatible with LEDiL
HEKLA


FN15972_RONDA-ZT45-C



Dimensions: 53.9 mm x 53.9 mm
Height: 16.60 mm

Double asymmetric beam for
wall-washing and aisle lighting with
holder C compatible with LEDiL
HEKLA


FN15973_RONDA-REC-60-C



Dimensions: 53.9 mm x 53.9 mm
Height: 16.60 mm

~60° + 60° rectangular beam with
holder C compatible with LEDiL
HEKLA


FN15974_RONDA-REC-90-C



Dimensions: 53.9 mm x 53.9 mm
Height: 16.60 mm

~80° rectangular beam with holder
C compatible with LEDiL HEKLA


FN15975_RONDA-WAS2-C



Dimensions: 53.9 mm x 53.9 mm
Height: 16.00 mm

Asymmetric beam ideal for floor
installations with holder C
compatible with LEDiL HEKLA

FN15977_RONDA-WAS2




Dimensions: 69.9 mm x 69.9 mm
Height: 14.60 mm

Asymmetric beam for wall-washing
with holder A compatible with TE,
Bender+Wirth and IDEAL

PRODUCTS:


FN15978_RONDA-WAS2-B



Dimensions: 69.9 mm x 69.9 mm
Height: 14.50 mm

Asymmetric beam for wall-washing
with holder B compatible with 3rd
party connectors from BJB, IDEAL
and Stucchi.


FN15993_RONDA-O



Dimensions: 69.9 mm x 69.9 mm
Height: 17.28 mm

~50° + 30° oval beam with holder A
compatible with 3rd party connectors
from TE, Bender+Wirth and IDEAL.


FN15997_RONDA-O-B



Dimensions: 69.9 mm x 69.9 mm
Height: 14.50 mm

~50° + 30° oval beam with holder B
compatible with 3rd party connectors
from BJB, IDEAL and Stucchi.


FN15998_RONDA-O-C



Dimensions: 53.9 mm x 53.9 mm
Height: 20.50 mm

~50° + 30° oval beam with holder C
compatible with LEDiL HEKLA


FN15380_RONDA-WAS



Dimensions: 69.9 mm x 69.9 mm
Height: 21.80 mm

Asymmetric beam for wall washing
with holder A compatible with 3rd
party connectors from TE,
Bender+Wirth and IDEAL

FN15381_RONDA-WWW




Dimensions: 69.9 mm x 69.9 mm
Height: 14.60 mm

~90° very wide beam with holder A
compatible with 3rd party connectors
from TE, Bender+Wirth and IDEAL

PRODUCTS:


FN15387_RONDA-WW



Dimensions: 69.9 mm x 69.9 mm
Height: 14.60 mm

~60° wide beam with holder A
compatible with 3rd party connectors
from TE, Bender+Wirth and IDEAL


FN15388_RONDA-ZT45



Dimensions: 69.9 mm x 69.9 mm
Height: 15.00 mm

Double asymmetric beam for
wall-washing and aisle lighting with
holder A compatible with 3rd party
connectors from TE, Bender+Wirth
and IDEAL


FN15552_RONDA-W



Dimensions: 69.9 mm x 69.9 mm
Height: 14.00 mm

~45° wide beam with holder A
compatible with 3rd party connectors
from TE, Bender+Wirth and IDEAL


FN15622_RONDA-REC-60



Dimensions: 69.9 mm x 69.9 mm
Height: 14.60 mm

~60° + 60° rectangular beam with
holder A compatible with 3rd party
connectors from TE, Bender+Wirth
and IDEAL


FN15679_RONDA-S



Dimensions: 69.9 mm x 69.9 mm
Height: 14.60 mm

~25° spot beam with holder A
compatible with 3rd party connectors
from TE, Bender+Wirth and IDEAL

FN15731_RONDA-WAS-B




Dimensions: 69.9 mm x 69.9 mm
Height: 22.30 mm

Asymmetric beam for wall washing
with holder B compatible with 3rd
party connectors from BJB, IDEAL
and Stucchi

PRODUCTS:


FN15733_RONDA-ZT45-B



Dimensions: 69.9 mm x 69.9 mm
Height: 15.40 mm

Double asymmetric beam for wall-washing and aisle lighting with holder B compatible with 3rd party connectors from BJB, IDEAL and Stucchi


FN15734_RONDA-S-B



Dimensions: 69.9 mm x 69.9 mm
Height: 14.60 mm

~25° spot beam with holder B compatible with 3rd party connectors from BJB, IDEAL and Stucchi

FN15735_RONDA-W-B



Dimensions: 69.9 mm x 69.9 mm
Height: 14.60 mm

~45° wide beam with holder B compatible with 3rd party connectors from BJB, IDEAL and Stucchi

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)