

STRADA-SQ-T-DN

Beam for area lighting with shorter illumination distances. Version with location pins. Optimized for CREE XP-E.

TECHNICAL SPECIFICATIONS:

Dimensions 25.0 mm Height 7.9 mm

Fastening glue, pin, screw

Colour clear

Box size 480 x 280 x 300 mm

Box weight 5.7 kg

Quantity in Box 2058 pcs

ROHS compliant yes 1




MATERIAL SPECIFICATIONS:

ComponentTypeMaterialColourSTRADA-SQ-T-DNSingle lensPMMAclear



PRODUCT DATASHEET

C11889_STRADA-SQ-T-DN




Last update: 21/05/2018

Subject to change without prior notice

PHOTOMETRIC DATA (MEASURED):

CREE 💠


LED XM-L
FWHM Asymmetric
Efficiency 92 %
Peak intensity cd/lm
LEDs/each optic 1
Light colour White
Required components:



CREE &

LED XP-G2
FWHM Asymmetric
Efficiency 93 %
Peak intensity 0.600 cd/lm
LEDs/each optic 1


LEDs/each optic 1 Light colour White Required components:



CREE 🕏

LED XP-L2
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.500 cd/lm

Peak intensity 0.500 c LEDs/each optic 1 Light colour White Required components:



CREE 🕏

LED XT-E

FWHM Asymmetric

Efficiency %
Peak intensity cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):



LED LUXEON A FWHM Asymmetric

Efficiency %
Peak intensity cd/lm
LEDs/each optic 1
Light colour White
Required components:

MILEDS

LED LUXEON Rebel ES


FWHM Asymmetric
Efficiency 92 %
Peak intensity cd/lm
LEDs/each optic 1
Light colour White
Required components:

PHOTOMETRIC DATA (SIMULATED):

CREE \$

LED XHP35 HD **FWHM** Asymmetric Efficiency 94 % Peak intensity 0.560 cd/lm


LEDs/each optic 1 Light colour White Required components:



CREE 🕏

LED XP-G3 **FWHM** Asymmetric 94 % Efficiency Peak intensity 0.700 cd/lm


LEDs/each optic 1 White Light colour Required components:



CREE ÷

LED XP-L HD **FWHM** Asymmetric Efficiency 93 %


Peak intensity cd/lm LEDs/each optic 1 Light colour White Required components:



SAMSUNG

LED LH351D **FWHM** Asymmetric Efficiency 94 % 0.640 cd/lm Peak intensity

LEDs/each optic 1 White Light colour Required components:





GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

www.ledil.com/ where_to_buy