

PRODUCT DATASHEET C12286_ANGIE-M

ANGIE-M

Colour

~20° medium beam

TECHNICAL SPECIFICATIONS:

Dimensions Ø 34.0 mm
Height 10.7 mm
Fastening glue, pin

Box size 480 x 280 x 300 mm

clear

Box weight 8.4 kg

Quantity in Box 1254 pcs

ROHS compliant yes 1




MATERIAL SPECIFICATIONS:

ComponentTypeMaterialColourANGIE-MMulti-lensPMMAclear



PRODUCT





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PRODUCT DATASHEET C12286_ANGIE-M

PHOTOMETRIC DATA (MEASURED):

CREE 💠

LED XP-E
FWHM 23.0°
Efficiency 86 %
Peak intensity 3.000 cd/lm
LEDs/each optic 1

Light colour White Required components:

CREE \$

LED XP-G
FWHM 24.0°
Efficiency 88 %
Peak intensity 4.620 cd/lm


LEDs/each optic 1 Light colour White Required components:

MUMILEDS

LED LUXEON T FWHM 22.0° Efficiency 90 % Peak intensity 4.400 cd/lm

LEDs/each optic 1 Light colour White Required components:






DESCRIPTION LUMILEDS

LED LUXEON TX
FWHM 22.0°
Efficiency 89 %
Peak intensity 4.800 cd/lm

LEDs/each optic 1
Light colour White
Required components:







PRODUCT DATASHEET C12286_ANGIE-M

PHOTOMETRIC DATA (MEASURED):

OSRAM Opto Semiconductors

LED

Oslon Square EC

FWHM 22.0° 88 % Efficiency Peak intensity 4.500 cd/lm LEDs/each optic 1

Light colour White Required components:

OSRAM Opto Semiconductors

LED Oslon SSL 150

FWHM 16.0° 91 % Efficiency Peak intensity 6.900 cd/lm

LEDs/each optic 1 White Light colour Required components:

OSRAM Opto Semiconductors

LED Oslon SSL 80

FWHM 16.0° Efficiency 87 % Peak intensity 6.300 cd/lm

LEDs/each optic 1 Light colour White Required components:


PRODUCT DATASHEET C12286_ANGIE-M

PHOTOMETRIC DATA (SIMULATED):

CREE 💠

LED XP-L HD
FWHM 25.0°
Efficiency 89 %
Peak intensity 3.600 cd/lm

LEDs/each optic 1
Light colour White
Required components:




MUMILEDS

LED LUXEON H50-2

FWHM 22.0° Efficiency 92 % Peak intensity 5.500 cd/lm

LEDs/each optic 1 Light colour White Required components:




WNICHIA

LED NVSxx19B/NVSxx19C

FWHM 23.0° Efficiency 93 % Peak intensity 4.660 cd/lm

LEDs/each optic 1
Light colour White
Required components:



SEOUL SEMICONDUCTOR


 LED
 Z5M1/Z5M2

 FWHM
 20.0°

 Efficiency
 92 %

 Peak intensity
 6.950 cd/lm

LEDs/each optic 1
Light colour White
Required components:





PRODUCT DATASHEET C12286 ANGIE-M

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

www.ledil.com/ where_to_buy