GRM21BR71H104KA01# "#" indicates a package specification code.














< List of part numbers with package codes > GRM21BR71H104KA01L , GRM21BR71H104KA01K

Shape



References

Packaging	Specifications	Minimum quantity
L	$_{\phi}$ 180mm Embossed taping	3000
K	ϕ 330mm Embossed taping	10000

Mass (typ.)		
1 piece	17mg	
φ 180mm Reel	102g	

Specifications

Capacitance	0.10μF ±10%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	±15.0%
Temperature range of temperature characteristics	-55 to 125℃
Operating temperature range	-55 to 125℃

1 of 2



Attention


1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued $without\ advance\ notice.\ Please\ check\ with\ our\ sales\ representatives\ or\ product\ engineers\ before\ ordering.$


 $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Chart of characteristic data (The charts below may show another part number which shares its characteristics.)














2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.