
KEMET Part Number: C430C475K3R5TA

(C430C475K3R5TABULK)



Ceramic, AxiMax, 4.7 uF, 10%, 25 V, X7R, AxiMax, Commercial Standard



General Information	
AxiMax	
AxiMax, Commercial Standard	
Yes	
Tin	
N/A	

Dimensions		
D	3.81mm MAX	
L	6.1mm MAX	
LL	25.4mm +0.025/-0.076mm	
F	0.51mm +0.025/-0.076mm	

Specifications	
Capacitance:	4.7 uF
Capacitance Tolerance:	10%
Voltage DC:	25 VDC
Dielectric Withstanding Voltage:	62.5 V
Temperature Range:	-55/+125C
Temperature Coefficient:	X7R
Dissipation Factor:	3.5%
Aging Rate:	3% Loss/Decade Hour
Insulation Resistance:	110 MOhms

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	200	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

