

16Amps. Schottky Barrier Rectifiers




Features:




- UL Recognized file # E-326243.
- Plastic material used carries underwriters laboratory classifications 94V-0.
- Metal silicon junction, majority carrier conduction.
- Low power loss, high efficiency.
- High current capability, low forward voltage drop.
- High surge capability.
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications.
- Guarding for overvoltage protection.
- High temperature soldering guaranteed:
260°C/10 seconds, 0.25 inches (6.35mm) from case

TO-220AC



Diameters : Inches (Millimetres)



Marking Diagram



MBR16XX = Specific Device Code
G = Green Compound
Y = Year
WW = Work Week

16Amps. Schottky Barrier Rectifiers



Mechanical Data

Cases : JEDEC TO-220AC moulded plastic body.
 Terminals : Pure tin plated, lead free solderable per MIL-STD-750, method 2026.
 Mounting position: Any.
 Mounting torque : 5 inches - lbs. maximum.

Maximum Rating and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.
 Single phase, half wave, 60Hz, resistive or inductive load.
 For capacitive load, derate current by 20%

Type Number	Symbol	MBR 16100	MBR 16150	MBR 1645	MBR 1660	Units
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	100	150	45	60	V
Maximum RMS Voltage	V_{RMS}	70	105	31	42	
Maximum DC Blocking Voltage	V_{DC}	100	150	45	60	
Maximum Average Forward Rectified Current at $T_C = 125^\circ\text{C}$	$I_{F(AV)}$	16				A
Peak Repetitive Forward Current (Rated V_R , Square Wave, 20KHz) at $T_C = 125^\circ\text{C}$	I_{FRM}	32				
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	150				
Peak Repetitive Reverse Surge Current (Note 2)	I_{RRM}	0.5		1	0.5	
Maximum Instantaneous Forward Voltage at: $I_F = 16\text{A}, T_A = 25^\circ\text{C}$ $I_F = 16\text{A}, T_A = 125^\circ\text{C}$	V_F	0.85 0.75	0.95 0.92	0.63 0.57	0.75 0.65	V
Maximum Instantaneous Reverse Current at Rated DC Blocking Voltage (Note 1) at $T_A = 25^\circ\text{C}$ at $T_A = 125^\circ\text{C}$	I_R	0.3 7.5	0.1 5	0.5 15	0.5 10	mA
Voltage Rate of Change (Rated V_R)	dV/dt	10,000				V/ μS
Typical Junction Capacitance	C_j	500				pF
Maximum Typical Thermal Resistance (Note 3)	$R_{\theta JC}$	3				$^\circ\text{C}/\text{W}$
Operating Junction Temperature Range	T_J	-65 to +150				$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-65 to +175				

Notes: 1. Pulse Test : 300 μs pulse width, 1% duty cycle.
 2. 2 μs pulse width, f = 1KHz.
 3. Mount on heatsink size of 2 x 3 x 0.25 Inches Al-Plate.




16Amps. Schottky Barrier Rectifiers




Ratings and Characteristic Curves (MBR1645 thru MBR16150)


Forward Current Derating Curve




Maximum Non-Repetitive Forward Surge Current



Typical Instantaneous Forward Characteristics




Typical Reverse Characteristics




16Amps. Schottky Barrier Rectifiers



Typical Junction Capacitance



Typical Transient Thermal Characteristics



Part Number Table

Description	Part Number
Diode, Schottky, 16A, 100V	MBR16100
Diode, Schottky, 16A, 150V	MBR16150
Diode, Schottky, 16A, 45V	MBR1645
Diode, Schottky, 16A, 60V	MBR1660

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2011.

