

### General information:

#### Application

- Indoor lighting;
  - Production of office troffers;
  - Interior lights; • Decorative and advertisement lighting;
  - Backlighting in commercial
- LED connection diagram - 3 parallel circuits.



### Description:

Module	
Power	18 W
Max. power	25.5 W
Max. current	450 mA
Number of LEDs	51 pcs
LED allocation	17S3P
Max luminous flux of the module*	2380-2580 lm
Aluminum PCB thickness	1.4 ±0.1 mm
Size of PCB	1145x14 mm
LED	
Model	2835
Power	0.5 W
Forward voltage	3.0-3.3 V
Forward current	150 mA
Luminous flux	60-65 lm
Ra (CRI):	80
Color temperature:	4700-5200K

\* at current 350 mA

LED module is equipped with 9 holes of 4 mm diameter designed for M3 screws or rivets.

Mounting on adhesive tape (13 mm wide, 1 mm thick) is available on request.

LED module has options for connection to push wire terminals.

Versions are available with color temperature from 2700 to 6500 K.

Versions are available with extra high CRI > 90.



LEDs on the module may be damaged by static electricity (ESD), take precautions. Don't connect the module to operating power supply unit – first connect the module to power supply unit, and then connect power supply unit to mains. Observe the correct polarity, incorrect connection may be damage LEDs. Module does not equip any current – limiting elements (resistors, drivers, current stabilizers). Do not expose LED module to mechanical stress, moisture, oil and corrosive environment.