


JENNY-FT65

Forward throwing beam with peak in 65°


TECHNICAL SPECIFICATIONS:

| | |
|-----------------|--------------------|
| Dimensions | 35.0 mm |
| Height | 15.4 mm |
| Fastening | pin |
| Colour | clear |
| Box size | 480 x 280 x 300 mm |
| Box weight | 8.4 kg |
| Quantity in Box | 1140 pcs |
| ROHS compliant | yes ⓘ |



MATERIAL SPECIFICATIONS:

| Component | Type | Material | Colour |
|------------|-------------|----------|--------|
| JENNY-FT65 | Single lens | Silicone | clear |




| INDEX | PART NO | DESCRIPTION | MATERIAL | COLOUR |
|-------|---------|-------------|------------------------|--------|
| 1 | F15909 | JENNY-FT65 | optical grade silicone | |

Tolerances if not otherwise shown
According to DIN ISO 2768-1
Linear measures:
Up to 30mm class M, otherwise class C.
According to DIN ISO 2768-2
Form and position: class L



Ledil Oy
Salorankatu 10
FIN 24240 SALO
Finland

THIRD ANGLE PROJECTION:



DRAWING TITLE

F15909_JENNY-FT65

This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy.

SIZE PART NUMBER

A4


F15909

SCALE 1:1 WEIGHT 5,96 g SHEET 1/1


PHOTOMETRIC DATA (MEASURED):







LED XHP70.2
FWHM Asymmetric
Efficiency 92 %
Peak intensity 0.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14436_JENNY-HLD-A-BLK



LED LUXEON M/MX
FWHM Asymmetric
Efficiency 90 %
Peak intensity 1.000 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14436_JENNY-HLD-A-BLK



PHOTOMETRIC DATA (SIMULATED):

| | |
|---|---|
| <p>LUMILEDS</p> <p>LED LUXEON MZ FWHM Asymmetric Efficiency 93 % Peak intensity 1.300 cd/lm LEDs/each optic 1 Light colour White Required components:</p> |  |
| <p>NICHIA</p> <p>LED NVSxE21A FWHM Asymmetric Efficiency 93 % Peak intensity 1.300 cd/lm LEDs/each optic 4 Light colour White Required components:</p> |  |
| <p>OSRAM <small>Opto Semiconductors</small></p> <p>LED Duris S8 FWHM Asymmetric Efficiency 94 % Peak intensity 1.300 cd/lm LEDs/each optic 1 Light colour White Required components:</p> |  |
| <p>OSRAM <small>Opto Semiconductors</small></p> <p>LED OSCONIQ P 3737 (2W version) FWHM Asymmetric Efficiency 94 % Peak intensity 1.480 cd/lm LEDs/each optic 1 Light colour White Required components:</p> |  |

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)