

JENNY-8X1-20

~20° beam. 8X1 variant.


TECHNICAL SPECIFICATIONS:

Dimensions	280.0 x 35.0 mm
Height	14.5 mm
Fastening	glue, pin
Colour	clear
Box size	398 x 298 x 265 mm
Box weight	10.5 kg
Quantity in Box	150 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:


Component	Type	Material	Colour
JENNY-8X1-20	Multi-lens	Silicone	clear




PHOTOMETRIC DATA (SIMULATED):




LED MHD-E/G
FWHM 24.0°
Efficiency 95 %
Peak intensity 3.720 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED MK-R
FWHM 14.0°
Efficiency 96 %
Peak intensity 6.430 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XHP70
FWHM 20.0°
Efficiency 96 %
Peak intensity 4.660 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED LUXEON M/MX
FWHM 16.0°
Efficiency 96 %
Peak intensity 6.290 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (SIMULATED):


OSRAM Opto Semiconductors

LED Duris S10
FWHM 21.0°
Efficiency 96 %
Peak intensity 5.080 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM Opto Semiconductors

LED OSCONIQ P 7070
FWHM 13.0°
Efficiency 96 %
Peak intensity 7.880 cd/lm
LEDs/each optic 1
Light colour White
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salu, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)