

STRADELLA-IP-28-HB-S-PC

~30° spot beam. Variant made from PC.



TECHNICAL SPECIFICATIONS:

Dimensions	100.0 mm
Height	9.5 mm
Fastening	pin, screw
Colour	clear
Box size	476 x 273 x 247 mm
Box weight	6 kg
Quantity in Box	156 pcs
ROHS compliant	yes ⓘ















MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
STRADELLA-IP-28-HB-S-PC	Multi-lens	PC	clear
STRADELLA-28-SEAL	Seal	Silicone	white





PHOTOMETRIC DATA (MEASURED):

<p></p> <p>LED HiQLED STR28 CR JE2835 4x7 xxx FWHM 22.0° Efficiency 83 % Peak intensity 1.900 cd/m LEDs/each optic 1 Light colour White Required components:</p>		
<p></p> <p>LED HiQLED STR28 CR JÐš3030 4x7 xxx FWHM 20.0° Efficiency 82 % Peak intensity 2.100 cd/m LEDs/each optic 1 Light colour White Required components:</p>		
<p></p> <p>LED QUICK FLUX STR28 XD2x14 xxx G8 FWHM 22.0° Efficiency 83 % Peak intensity 1.700 cd/m LEDs/each optic 1 Light colour White Required components:</p>		
<p></p> <p>LED QUICK FLUX STR28 XP2x14 xxx G7 FWHM 30.0° Efficiency 89 % Peak intensity 1.300 cd/m LEDs/each optic 1 Light colour White Required components:</p>		


PHOTOMETRIC DATA (MEASURED):





LED QUICK FLUX STR28 XT2x14 xxx G5
FWHM 29.0°
Efficiency 86 %
Peak intensity 1.500 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED J Series 2835
FWHM 22.0°
Efficiency 83 %
Peak intensity 1.900 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED J Series 3030
FWHM 20.0°
Efficiency 82 %
Peak intensity 2.100 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED XD16
FWHM 22.0°
Efficiency 83 %
Peak intensity 1.700 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):





LED XP-G3
 FWHM 30.0°
 Efficiency 84 %
 Peak intensity 1.300 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED XT-E
 FWHM 29.0°
 Efficiency 86 %
 Peak intensity 1.500 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED HiLOM SC28 (LH181B)
 FWHM 21.0°
 Efficiency 80 %
 Peak intensity 1.800 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED HiLOM SM28 (LM301B)
 FWHM 23.0°
 Efficiency 83 %
 Peak intensity 1.800 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




PHOTOMETRIC DATA (SIMULATED):




LED LUXEON 3030 2D (Round LES)
 FWHM 25.0°
 Efficiency 89 %
 Peak intensity 2.204 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED NF2x757G
 FWHM 27.0°
 Efficiency 91 %
 Peak intensity 2.150 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED NVSxE21A
 FWHM 23.0°
 Efficiency 89 %
 Peak intensity 2.384 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED OSCONIQ P 3737 (3W version)
 FWHM 34.0°
 Efficiency 90 %
 Peak intensity 1.500 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



PHOTOMETRIC DATA (SIMULATED):


OSRAM
Opto Semiconductors

LED OSLON Square CSSRM2/CSSRM3
 FWHM 27.0°
 Efficiency 85 %
 Peak intensity 1.780 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




SEOL
SEOUL SEMICONDUCTOR

LED Z5M1/Z5M2
 FWHM 27.0°
 Efficiency 87 %
 Peak intensity 2.070 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




SEOL
SEOUL SEMICONDUCTOR

LED Z8Y19
 FWHM 24.0°
 Efficiency 82 %
 Peak intensity 1.920 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



SEOL
SEOUL SEMICONDUCTOR

LED Z8Y22
 FWHM 28.0°
 Efficiency 89 %
 Peak intensity 1.629 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)